



**DESCRIPTION:** THE PULL BOX IS USED WHERE REMOTE EMERGENCY MANUAL OPERATION OF A SYSTEM IS REQUIRED. THE HANDLE IS CONNECTED TO THE GAS RELEASE DEVICE BY FLEXIBLE PHOSPHOR BRONZE CABLE RUN IN MILD STEEL CONDUIT FOR PROTECTION. ABRUPT CHANGES IN DIRECTION TO THE ROUTING OF THE MANUAL PULL LINE ARE EFFECTED BY MEANS OF ENCLOSED BRASS PULLEYS.

**MATERIAL:** BOX-STEEL  
FRONT COVER-PLASTIC

**TEMPERATURE RANGE:** -30°C to +55°C

**WEIGHT:** 1.65Kg

**FINISH:** PAINTED RED

**ENVIRONMENT:** PROTECTED FROM THE ELEMENTS.  
DESIGNED TO MEET BS5490 I.P.40.

NOTE: - REPLACEMENT BREAK GLASS AVAILABLE. USE PART NUMBER K1120.

ALL DIMENSIONS IN mm's UNLESS OTHERWISE STATED

**MECHANICAL PULL BOX ACCESSORIES**

K9002	CABLE 1/8" PHOS.BRONZE(PER METRE)
K1122	CORNER PULLEY 1/8"(STANDARD)
K3092	CABLE CLAMP(1/8" CABLE)
K90001	1/2" O/D CONDUIT GALV.(PER METRE)
K90106	1/4" BRASS NIPPLE
K10171	1/4" BRASS RING BUSH
K90183	1/4" BRASS UNION
K90197	1/4" BRASS SOCKET
K90202	1/4" BRASS BACKNUT

2	10.09.04	REISSUE	M.M.
1	MAY'93	ORIGINAL ISSUE	
REV	DATE	REASON FOR ISSUE	APP