



22MM METAL ROUND COMPLETE UNIT COMBINATION:
 PUSHBUTTON MOMENTARY CONTACT TYPE WITH
 FLAT BUTTON SCREW TERMINAL,
 1NO WITH HOLDER BLACK SOLVENT RESISTANT

Actuator:

Design of the operating mechanism		pushbutton switch, flat
Manner of function / of the activation element		
<ul style="list-style-type: none"> • arresting lock • tentative 		No
		Yes

Button:

Design of the button		flat
Color / of the button		black

Front ring:

Product component / front ring		Yes
Material / of the front ring		metal
Color / of the front ring		silver

Enclosure:

Shape / of the housing front		round
material / of the housing		metal

General technical details:

Design of the product		pushbutton with flat button
Type of voltage		

• of the operating voltage		AC/DC
Operating voltage		
• rated value	V	5 ... 400
Design of the electrical connection		screw-type terminals
Number of switching positions		2
Resistance against shock		
• for devices without incandescent lamp / according to IEC 60068-2-27		<= 50g
Resistance against vibration / according to IEC 60068-2-6		20 ... 200 Hz: 5g
Operating cycles / maximum	1/h	1,000
Mechanical operating cycles as operating time / typical		10,000,000
Product extension / optional / fluorescent materials		No
Item designation		
• according to DIN EN 61346-2		S
• according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		S

Auxiliary Contacts:

Number of NC contacts / for auxiliary contacts		0
Number of NO contacts / for auxiliary contacts		1
Number of change-over switches / for auxiliary contacts		0

Installation/mounting/dimensions:

Type of mounting		front mounting
Shape / of the installation hole		round
Mounting diameter	mm	22
Width	mm	30
Height	mm	36.5
Depth	mm	61
Tightening torque / of the screws in the bracket / maximum	N·m	1

Ambient conditions:

Ambient temperature		
• during operating	°C	-25 ... 70
• during storage	°C	-40 ... 80
Climatic class / according to DIN EN ISO 6270-2		KTW24
Protection class IP		IP67

Certificates/approvals:

General Product Approval



CQC

[ROSTEST](#)



UL

Test Certificates

[Manufacturer](#)

Shipping Approval



ABS



BUREAU
VERITAS



DNV



LRS



RINA

other

[Manufacturer](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3SB3602-0AA11/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3SB3602-0AA11

last change:

Oct 31, 2011