


Victaulic® Duplex Grooved Couplings

Style 77DX Duplex Stainless Steel Flexible Coupling



1.0 PRODUCT DESCRIPTION

Available Sizes:

- ¾ – 6"/DN20 – DN150

NOTE

- For 8 – 18"/DN200 – DN450 sizes, Victaulic offers stainless steel couplings. See [publication 17.03](#) for the Style 77S Stainless Steel Flexible Coupling.

Maximum Working Pressure:

- Up to 1200 psi/8273 kPa on ANSI wall thickness
- Up to 750 psi/5171 kPa on ISO wall thickness

83 bar

Application:

- Joins standard roll grooved and cut grooved pipe, as well as grooved fittings, valves and accessories

Pipe Material:

- Roll grooved Type 304/316 stainless steel
- Cut grooved duplex/super duplex stainless steel

2.0 CERTIFICATION/LISTINGS

Product designed and manufactured under the Victaulic Quality Management System, as certified by LPCB in accordance with ISO-9001:2008.

ALWAYS REFER TO ANY NOTIFICATIONS AT THE END OF THIS DOCUMENT REGARDING PRODUCT INSTALLATION, MAINTENANCE OR SUPPORT.

System No.		Location	
Submitted By		Date	

Spec Section		Paragraph	
Approved		Date	