

SIMATIC DP, INTERFACE IM 153-1, FOR ET 200M, FOR MAX. 8 S7-300 MODULES



Figure similar

General information	
Vendor identification (VendorID)	801Dh
Supply voltage	
Rated value (DC)	24 V
• 24 V DC	Yes
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
permissible range (ripple included), lower limit (DC)	20.4 V
permissible range (ripple included), upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	not necessary
Mains buffering	
• Mains/voltage failure stored energy time	5 ms
Input current	
Current consumption, max.	350 mA; at 24 V DC
Inrush current, typ.	2.5 A
I ² t	0.1 A ² ·s

Output voltage	
Rated value (DC)	5 V
Output current	
for backplane bus (5 V DC), max.	1 A
Power loss	
Power loss, typ.	3 W
Address area	
Addressing volume	
• Inputs	128 byte
• Outputs	128 byte
Hardware configuration	
Number of modules per DP slave interface, max.	8
Interfaces	
Transmission procedure	RS 485
Interface physics, RS 485	Yes
Interface physics, FOC	No
PROFIBUS DP	
• Node addresses	1 to 125 permitted
• automatic detection of transmission rate	Yes
• Output current, max.	90 mA
• Transmission rate, max.	12 Mbit/s
• SYNC capability	Yes
• FREEZE capability	Yes
• Direct data exchange (slave-to-slave communication)	Yes; Sender
• Connector type	9-pin sub D socket
1. Interface	
DP slave	
• GSD file	(for DPV1) SIEM801D.GSD; SI01801D.GSG
• automatic baud rate search	Yes
Protocols	
Bus protocol/transmission protocol	PROFIBUS DP to EN 50170
Isolation	
Isolation tested with	Isolation voltage 500 V
Degree and class of protection	
Degree of protection acc. to EN 60529	
• IP20	Yes
Ambient conditions	

Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
Air pressure acc. to IEC 60068-2-13	
• Installation altitude above sea level, max.	3 000 m

Configuration	
Configuration software	
• STEP 7	STEP 7 / COM PROFIBUS / non-Siemens tools via GSD file

Dimensions	
Width	40 mm
Height	125 mm
Depth	117 mm

Weights	
Weight, approx.	360 g
last modified:	08/12/2017